

品種一覧

PLEシリーズ

形名	温度特性	静電容量 (pF)	静電容量許容差	使用温度範囲	定格電圧 (Vdc)	絶縁抵抗 MΩmin.
PLE123	SL	10	±1pF	-25~+85°C	50	5,000
PLE123	SL	22	±20%	-25~+85°C	50	5,000
PLE123	YE	220	+100,-0%	-25~+85°C	50	5,000
PLE123	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE12	SL	1	±1pF	-25~+85°C	50	5,000
PLE12	SL	10	±1pF	-25~+85°C	50	5,000
PLE12	YE	470	+100,-0%	-25~+85°C	50	5,000
PLE12	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE22	SL	5	±1pF	-25~+85°C	50	5,000
PLE22	SL	22	±20%	-25~+85°C	50	5,000
PLE22	YN	47	±20%	-25~+85°C	50	5,000
PLE22	YN	100	±20%	-25~+85°C	50	5,000
PLE22	YE	470	±20%	-25~+85°C	50	5,000
PLE22	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE22	YF	2,000	+100,-0%	-25~+85°C	50	5,000
PLE32	X7R	1,200	±20%	-55~+125°C	50	5,000
PLE32	YF	3,000	+80,-20%	-25~+85°C	50	5,000
PLE255	X7R	1,000	+100,-0%	-55~+125°C	50	5,000
PLE255	YF	4,700	+80,-20%	-25~+85°C	50	5,000
PLE23	SL	2	±1pF	-25~+85°C	50	5,000
PLE23	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE23	YF	2,000	+100,-0%	-25~+85°C	50	5,000
PLE33	SL	100	±20%	-25~+85°C	50	5,000
PLE33	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE33	YF	2,200	+100,-0%	-25~+85°C	50	5,000
PLE335	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE335	YF	2,000	+100,-0%	-25~+85°C	50	5,000

上記表中以外の形状、静電容量値も対応可能です。詳しくは弊社営業部までお問い合わせください。