

品種一覧

■定格電圧 630V DC

形名	静電容量(μF)	T寸法(mm)
RC30R2J472K-TPN	0.0047	1.25+0/-0.30
RC30R2J103K-TPN	0.010	1.35+0/-0.40
RC40R2J103K-TPN	0.010	1.25+0/-0.30
RC40R2J223K-TPN	0.022	2.20+0/-0.50
RC40R2J473K-TPN	0.047	2.50+0/-0.60
RC70R2J473K-TPN	0.047	1.70+0/-0.40
RC70R2J104K-TPN	0.10	2.80+0/-0.60
RC80R2J104K-TPN	0.10	1.70+0/-0.40
RC80R2J224K-TPN	0.22	2.80+0/-0.60

■定格電圧 250V DC

形名	静電容量(μF)	T寸法(mm)
RC30R2E223K-TPN	0.022	1.00+0/-0.25
RC30R2E473K-TPN	0.047	1.80+0/-0.40
RC40R2E473K-TPN	0.047	1.00+0/-0.25
RC40R2E104K-TPN	0.1	1.70+0/-0.40
RC40R2E224K-TPN	0.22	2.50+0/-0.60
RC70R2E104K-TPN	0.1	1.00+0/-0.25
RC70R2E224K-TPN	0.22	1.70+0/-0.40
RC70R2E474K-TPN	0.47	2.80+0/-0.60
RC80R2E224K-TPN	0.22	1.25+0/-0.30
RC80R2E474K-TPN	0.47	1.70+0/-0.40
RC80R2E105K-TPN	1	2.80+0/-0.60

■定格電圧 100V DC

形名	静電容量(μF)	T寸法(mm)
RC30R2A104K-TPN	0.1	1.00+0/-0.25
RC30R2A224K-TPN	0.22	1.80+0/-0.40
RC30R2A105K-TPL	1	1.80+0/-0.40
RC40R2A224K-TPN	0.22	1.00+0/-0.25
RC40R2A474K-TPN	0.47	1.70+0/-0.40
RC40R2A105K-TPN	1	2.50+0/-0.60
RC70R2A474K-TPN	0.47	1.25+0/-0.30
RC70R2A105K-TPN	1	1.70+0/-0.40
RC70R2A225K-TPN	2.2	2.80+0/-0.60
RC80R2A105K-TPN	1	1.25+0/-0.30
RC80R2A225K-TPN	2.2	1.70+0/-0.40
RC80R2A475K-TPN	4.7	2.80+0/-0.60

■定格電圧 50V DC

形名	静電容量(μF)	T寸法(mm)
RC20R1H105K-TPL	1	1.25±0.20
RC30R1H104K-TPN	0.1	1.00+0/-0.25
RC30R1H224K-TPN	0.22	1.00+0/-0.25
RC30R1H474K-TPN	0.47	1.80+0/-0.40
RC30R1H105K-TPL	1.00	1.60±0.2
RC30R1H475K-TPL	4.70	1.60±0.2
RC40R1H474K-TPN	0.47	1.25+0/-0.30
RC40R1H105K-TPL	1.0	2.50±0.30
RC40R1H225K-TPN	2.2	2.50+0/-0.60
RC40R1H475K-TPL	4.7	2.50±0.30
RC70R1H105K-TPN	1	1.25+0/-0.30
RC70R1H225K-TPN	2.2	1.70+0/-0.40
RC70R1H475K-TPN	4.7	2.80+0/-0.60
RC80R1H225K-TPN	2.2	1.25+0/-0.30
RC80R1H475K-TPN	4.7	1.70+0/-0.40
RC80R1H106K-TPN	10	2.80+0/-0.60

品種一覧

■定格電圧 25V DC

形名	静電容量(μF)	T寸法(mm)
RC20R1E105K-TPL	1.0	1.25±0.20
RC30R1E105K-TPL	1.0	1.60±0.20
RC30R1E225K-TPL	2.2	1.60±0.20
RC30R1E475K-TPL	4.7	1.60±0.20
RC30R1E106K-TPL	10	1.60±0.20
RC40R1E105K-TPL	1.0	1.25±0.20
RC40R1E225K-TPL	2.2	2.00±0.20
RC40R1E475K-TPL	4.7	2.50±0.30
RC40R1E106K-TPL	10	2.50±0.30

■定格電圧 16V DC

形名	静電容量(μF)	T寸法(mm)
RC10R1C105K-TPL	1.0	0.80±0.10
RC20R1C105M-TPL	1.0	1.25±0.20
RC20R1C225K-TPL	2.2	1.25±0.20
RC30R1C105K-TPL	1.0	1.25±0.20
RC30R1C225K-TPL	2.2	1.60±0.20
RC30R1C475K-TPL	4.7	1.60±0.20
RC30R1C106K-TPL	10	1.60±0.20
RC40R1C475K-TPL	4.7	2.00±0.20
RC40R1C106K-TPL	10	2.50±0.30

■定格電圧 10V DC

形名	静電容量(μF)	T寸法(mm)
RC20R1A105K-TPL	1.0	1.25±0.20
RC20R1A225K-TPL	2.2	1.25±0.20
RC30R1A475K-TPL	4.7	1.60±0.20
RC30R1A106K-TPL	10	1.60±0.20
RC40R1A106K-TPL	10	2.00±0.20

■定格電圧 6.3V DC

形名	静電容量(μF)	T寸法(mm)
RC10R0J105K-TPL	1.0	0.80±0.10
RC10R0J225K-TPL	2.2	0.80±0.10
RC20R0J475K-TPL	4.7	1.25±0.20
RC20R0J106K-TPL	10	1.25±0.20
RC30R0J106K-TPL	10	1.60±0.20